



## Benefits

- 1U 19" widescreen LCD console drawer
- 1440 x 900 native resolution / 16.7M colors
- DVI-D + VGA video input / USB KB / MS
- 104-key keyboard with either touchpad or trackball
- Short depth design of 460mm
- One Man installation design
- New enhanced aesthetics with molded front handle
- 2-year standard warranty ( upgradable up to 5 years )

## Options

- Front USB hub port for device access
- HDMI 1.2 video input
- S-Video + Composite ( BNC )
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available
- 2-post rack mounting brackets ( ORB-2.1 )

## Product Specifications

Console Port	
Video input	VGA + DVI-D single link
KB / MS	Combo ( USB or PS2 )
VGA console 6ft cable : CB-6 or DVI-D console 6ft cable : CX-6	Drawer end : DB-15 ( VGA + USB KB / MS ) Server end : VGA + USB type A  Drawer end : DVI-D + DB-15 ( USB KB / MS ) Server end : DVI-D + USB type A

LCD Panel		Physical		
Panel size ( diagonal )	19"	Product ( W x D x H )	Single console	442 x 460 x 44 mm 17.4 x 18.1 x 1.73 inch
Native resolution	1440 x 900		Console w/ KVM	442 x 580 x 44 mm 17.4 x 22.8 x 1.73 inch
Brightness ( cd/m <sup>2</sup> )	300	Packing ( W x D x H )	Single console / Console w/ KVM	590 x 808 x 140 mm 23.2 x 31.8 x 5.5 inch
Contrast ratio ( typ. )	1000 : 1		Net weight	Single console
Colors	16.7 M	Gross weight	Console w/ KVM	12.5 kg / 28 lb
Viewing angle ( L/R/U/D )	80/80/80/80		Single console	16 kg / 35.2 lb
Response time ( ms )	5	Console w/ KVM	18.1 kg / 39.8 lb	
Dot pitch ( mm )	0.2835	<b>Mounting Distance</b>		
Display area ( mm )	408.24H x 255.15V	Single console drawer	470 ~ 700 mm 18.5 ~ 27.6 inch	
Surface treatment	Haze 25%, Hard-coating			
Surface hardness	3H			
Backlight type	CCFL			
MTBF (hrs)	50,000			


Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 25W / Max. 55W
	Power saving mode	Max. 4W / Max. 34W
	Power button on	Max. 1W / Nil

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	5~500Hz 1G RMS random vibration

OEM - Austin Huges

Compliance	
EMC	FCC & CE certified
Safety	c UL us & CE / LVD certified
Environment	RoHS2 & REACH compliant




**DVI-D USB KVM Cable**



CI - 6 ( 6 ft )  
CI - 15 ( 15 ft )

\*6 feet DVI-D Console Cable  
Server end - DVI-D+USB  
Console port - DVI-D+DB15 (USB KB+MS)

**DB-15 VGA USB KVM Cable**

CB - ( 66 ft )      CB - 10 ( 10 ft )      CB - 15 ( 15 ft )

\*6 feet VGA Console Cable  
Server end - VGA+USB  
Console port - DB15 (VGA, USB KB & MS)

**Standard Keyboard**

**Ge** G keyboard integrated with touchpad

